PENCOM Self-Clinching Stud Application Guide

| | Installation Type | | | Available Stud Material(s) | | | | | Installation Sheet Material(s) | | | | |
|--------|-------------------|-----------|-------------------------------|----------------------------|--------------------|------------------------------|----------------------------------|--|--------------------------------|-----------------|--------------------|---------------|---------------------------------------|
| Series | Self-Clinching | Broaching | Minimum Sheet Thickness | Aluminum | Phosphor Bronze | Heat Treated Carbon Steel | 300-Series Stainless Steel | Heat Treated 400-Series Stainless Steel | Aluminum | Carbon Steel | Stainless Steel | P.C. Board | Special Feature |
| SA | ✓ | | .062" (1.57mm) | ✓ | | ✓ | ✓ | | ✓ | ✓ | | | Concealed head |
| SB | ✓ | | .040" (1.02mm) | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | Largest selection |
| SC | ✓ | | .020" (0.51mm) | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | For use in thin sheets |
| SD | ✓ | | .050" (1.27mm) | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | High-Strength |
| SE | ✓ | | .040" (1.02mm) | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | For use in close-to-edge applications |
| SF | ✓ | | .040" (1.02mm) | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | High-Strength |
| SG | | ✓ | .060" (1.53mm) | | ✓ | ✓ | ✓ | | ✓ | ✓ | | ✓ | |